



LANBASED L-PS-7008G-B

- \* 8 10/100/1000BaseT(X) Data-In Ports +  
8 10/100/1000BaseT(X) Data and Power-Out Ports
- \* 19" Rack-Mount Size
- \* Internal Power Supply

## 8-pair Port Rack-mount PoE Mid-span Power Supply

### Introduction

L-PS-7008G-B is 8-pair Port Rack-mount Power over Ethernet Mid-span Power Supply that is designed to help simplify network maintenance and for small or medium network environment to strengthen its network connection. Including rack-mount brackets, the 19" size fits into your rack environment. It is a superb choice to boost your network with better performance and efficiency.

### IEEE 802.3af/at Power over Ethernet (PoE) ports

L-PS-7008G-B features 8 10/100/1000BaseT(X) Data-In ports and 8 IEEE 802.3af/at Power over Ethernet (PoE) ports supplying up to 15.4 / 30 watts per port. This product can convert standard 100~240V/AC power into low-voltage DC that runs over existing LAN cable to power up IEEE 802.3af/at compliant network accessories. It also features PoE awareness to verify whether the network device receive power is IEEE 802.3af/at compliant, or only the data will be sent through LAN cable. By adding L-PS-7008G-B to existing networking, installing networking products such as Access Points and IP cameras can be easily managed and set up. Wireless device deployments are easily located with available power outlets and network administrators don't need to use heavy AC power adapters anymore.

### No Special Networking Cable Required

By adding PoE devices, you can use an existing standard Cat-5 Ethernet cable without a new electrical outlet for both power and data. It helps you reduce installation time and cost.

### Technical Specifications

<b>Standards</b>	IEEE 802.3af/at
<b>Features</b>	Number of Ports: 8 10/100/1000BaseT(X) Data-In Ports 8 10/100/1000BaseT(X) Data and Power-Out Ports
<b>Led Indicators</b>	Per Port: PoE Act/Status Per Unit: Power
<b>Power Input</b>	100~240V/AC, 50~60Hz
<b>Power Output</b>	56V/DC Per Port Output – 15.4/ 30 W Max Per Port 8 Ports at Full 15.4 / 30W Output Supported
<b>Power Consumption</b>	130 Watts (Max)
<b>Dimensions</b>	440 x 220 x 44 mm (W x D x H)
<b>Weight</b>	2.7 kg
<b>Operating Temperature</b>	0 to 40°C
<b>Storage Temperature</b>	-20 to 90°C
<b>Humidity</b>	10 to 90% RH (non-condensing)
<b>Certifications</b>	FCC Class A, CE