

Publish Date : 28.07.2019 | Rev no: 01

PowerMAX+ 2mtr Cat.6A F/UTP Patch Cord - PVC

DINTEK PowerMAX+™ Foil Wrapped UTP Patch Cords, are key components of the PowerMAX+™ F/UTP end-to-end solution.

DINTEK PowerMAX+™ F/UTP Patch Cords are specifically designed to support high speed data networks for 10-Gigabit Ethernet applications, and are fully tested to meet ANSI/TIA-568.2-D Category 6A channel requirements. The patch cables are made from high quality shielded four pair 26AWG stranded wire.

DINTEK PowerMAX+™ patch cords are pre-terminated with RJ45 shielded plugs and feature anti-snap strain relief boots. DINTEK recommends the entire range of PowerMAX+™ Shielded products be used in a end-to-end system to maximize cabling performance.

Applications

- 10GBASE-T Ethernet
- 100BASE-TX Fast Ethernet
- 1000BASE-TX Gigabit Ethernet
- 1000BASE-T Gigabit Ethernet
- 10BASE-TX Ethernet
- ATM CB1G
- 155/622 Mbps ATM
- 100 Mbps TP-PMD
- 100VG-AnyLAN
- 4/16 Mbps Token Ring
- Voice




Features

- Component Level Performance
- Molded boots prevent pin from bending and cables from kinking
- Stranded wire provides maximum flexibility
- Fully tested to meet ANSI/TIA-568.2-D category 6A requirement
- The mechanical characteristics and transmission performance meet
- 10GbaseT Ethernet, 16Mbps token Ring, 10Base-T, 100Base
- T, 155Mbps, 622Mbps ATM, Gigabit-Ethernet and 1.2Gbps ATM

Standards Conformance

- UL Listed
- Meet Cat.6A channel performance for in ANSI/TIA-568.2-D
- CENELEC EN 50173-1, CENELEC EN 50288-10-1
- ISO/IEC 2nd Edition 11801 Class EA
- RoHS-6 Compliant



Ordering Information

Product Number	Product Name	Jacket Type	Color	Length Qty
1201-06002	Cat.6A 4 Pair F/UTP Patch Cord Component Level	PVC	Gray	2 m
1201-06001	Cat.6A 4 Pair F/UTP Patch Cord Component Level	PVC	Gray	1 m
1201-06003	Cat.6A 4 Pair F/UTP Patch Cord Component Level	PVC	Gray	3 m
1201-06005	Cat.6A 4 Pair F/UTP Patch Cord Component Level	PVC	Gray	5 m

Technical Specifications

Cable Construction	
Conductor	
Material	Stranded anneal copper wire
Wire Size	26AWG
Insulation	
Material	Polyolefin
Diameter	0.96±0.05mm
Colors	Blue/White-Blue Orange/White-Orange Green/White-Green Brown/White-Brown
Diameter of dielectric core	P1&P3: 0.94±0.005mm P2&P4: 0.92±0.005mm
Jacket	
Material	PVC
Diameter	6.0±0.15mm
Color	Gray
Shielding Material	Aluminum Mylar(Aluminum inward)
Drain Wire	26AWG Tinned Copper
RJ45 Plug	
Plug Type	Shielded RJ45 plug
Contact Material	Copper alloy 50u" gold plated over nickel
Strength	20lbs. min
Durability	750 cycles min.
Wiring schemes	T568B (or T568A on request)
Electrical	
Impedance	15Ω/100m at 20°C
Capacitance unbalance pair to ground	330pf/100m Max
D.C.R (Max.)	14.8 ohm/100m at 20°C
DC Insulation Resistance	1500MΩ/100m min.
Resistance unbalance	3% MAX./100m

DINTEK Electronic Limited

5F., No.8, Ln. 97, Wugong Rd.
Xinzhuang Dist., New Taipei City 242
Taiwan (R.O.C.)

P: Office: +886-2-22997898 E-mail: sales@dintek.com.tw W: www.dintek.com.tw

1201-06002