EPICA EN-1400 6Gb SATA NAS EN-1400A6B-CM



As the number of users and the amount of data grows, how to find a storage which can offer complete data protection, good performance, with reliability and high scalability is the key for all enterprises and companies.

The EN-1400 6G SATA NAS based on latest proNAS 3.6 operating system. Except for basic NAS functions, it supports a variety of advanced storage management and application features such as VAAI, Thin-Provisioning, etc, and it can be deployed easily in any IT environment since it supports multiple interfaces for different host server and clients.

For data protection, EN-1400 supports RAID level 0, 1, 5, 6, 10 and Linear(JBOD) mode, and drives can be set hot spares, have automatically hot rebuilding and online capacity expansion within the enclosure. EN-1400 has a fully-featured backup solution including manual or scheduled backup for file, folder, and shares, and it can be backup and restore from multiple local or remote devices. And there are volume clone, snapshot, remote replication, and data copy for options, which are all designed to ensure and enhance your precious data.

Features

- Account Manager support NIS
- Allows online capacity expansion within the enclosure
- Backup to Cloud (Amazon S3)
- Backup/Restore from attached storage (USB/eSATA/iSCSI/RDX/USM)
- Backup/Restore from remote share (CIFS/NFS)
- Bonjour Protocol, easily connect to NAS
- Compression (Support on ZFS file system)
- Central data and storage management
- Data backup via backup plan/schedule
- Data copy (1:1)
- Deduplication (Support on ZFS file system)
- EXT4 support extend over 16TB

www.proware.com.tw

- iSCSI/share volume replication
- ISO mount

- Latest volume snapshot technology
- Local and external account management, support large account import

- Online expansion file system
- Plug-in management
- Select share or file for backup/restore
- Share management and permission
- (support ACL setting)
- Support Internet Gateway
- Support iSCSI target for IP SAN
- Support iSCSI initiator
- Support iSCSI multi host
- Support e-mail notification, SNMP Trap/MIB and system log
- System configuration backup/restore
- Thin Provisioning
- Volume Clone (EXT3/EXT4/XFS/NTFS/VMFS/ ZFS/Btrfs)
- Volume replication to enhance data protection
- VMware ESXi 5 iSCSI/NFS VAAI support
- Wizard-oriented GUI design
- WORM (Write Once Read Many) support CIFS/NFS

Series Technical Specifications

EN-1400A6B-CM

NAS Hardware Specification

ntel Celeron 2.8GHz or above	Support drive hot spare and automatic hot rebuild
Optional: Intel Pentium, Core i3 / i5 / i7	Locally audible event notification alarm
Cache memory : 8GB DDR4 SDRAM up to 32GB	Power requirements
Four USB3.0 and two USB2.0 ports	AC 100V ~ 240V Full range
Two Gigabit Ethernet ports	6A~3A, 60~50Hz
Support RAID level: RAID 0, 1, 5, 6, 10 and Linear(JBOD)	Environmental
Up to Four (4) 2.5"/3.5" hot-swappable 6Gb/s SATA3 hard drives	Relative humidity : 10%~85% Non-condensing
Real-time drive activity and status indicators	Operating temp : 10°C~40°C(50°F~104°F)
Environmental monitoring unit	Physical Dimension: 44(H) x 446.4(W) x 500(D)mm
250W power supply with PFC	Weight: 7.8kg (without drives)
NAS Functionality	
Storage Management	Microsoft Active Directory Authentication (ADS)
/olume management (Support Btrfs, ZFS, XFS, EXT3 and EXT4 file	Network Information Service (NIS)
system)	Support OpenLDAP service
Support Compression and Deduplication (Support on ZFS file	Support creating users by batch
system)	User quota management
Disk usage statistics	Share level security
Hot spare drives	File level security
SCSI Target manager: Support LUN Mapping/Initiator Filter/Thin	User ID security for NFS
Provisioning	Recycle bin (Samba)
/AAI support for iSCSI/NFS	File access log, audit (Samba)
General	Write Once Read Many (WORM)
ndependent file server	Block Storage
Nultiple language support	iSCSI Target Support
Support UPS	Thin Provisioning support
Support LV encryption	VMware VAAI support
System Management	Virtualization
Automatic IP address configuration	VMware/Citrix/Hyper-V
Neb browser-based management	VMware VAAI for NFS support
SNMP management and notification	Attached Storage
Fail-free online firmware upgrade	ISO Mount
Jnicode support	USB/eSATA/iSCSI initiator
Multi-node management GUI	Data Backup / Restore
System configuration backup/restore	Volume Clone (EXT3/EXT4/XFS/NTFS/VMFS/ZFS/Btrfs
Central management	Symantec BackupExec Agent (by additional installation)
Quick wizard	Scheduling multi-snapshot (Support iSCSI snapshot)
Networking	Replication (Remote realtime data mirroring)
Support NIC/Trunking/Load Balance/Fail Over/802.3ad	Scheduling Rsync Replication
DHCP Server/DHCP Client	Support NetVault backup client (by additional installation)
WINS Server	Support CA ARCserve (by additional installation)
nternet gateway	Data copy (copy files to other share/attached storage)
DDNS	Scheduling backup
Protocols	Differential/incremental backup
ICP/IP, SMB/CIFS, NFS, SNMP, FTP/SFTP/FXP, HTTP, HTTPS,	iSCSI Replication
Felnet, SSH, AFP, WebDAV, Bonjour, TFTP	Amazon S3 backup
Client Operating Systems Support	backup/restore from attached storage
Microsoft® Windows® 98/ME/NT/2000/XP/2003/Vista/2008/Win7/	(USB/eSATA/iSCSI/RDX*/USM*)
Nindows 2012/Win 8/Win 10/2016	Support Apple Time Machine
Jnix/Linux	Plug-in management
Mac OS	Anti-Virus
Authentication	Central management
Local user account/group	iTunes Server
5 1	

* By OEM request.

Specification are subject to change without notice. All company and product names are trademarks of their respective owners.

