

TD-E2128-L/TP

2MP HD Indoor Face Recognition Terminal



- 8 inch LCD touch screen
- Embedded man-machine interactive system
- Face liveness detection technology distinguishing real faces from non-real face spoof attacks
- Highly accurate face recognition using deep learning algorithm
- Special cameras for face recognition, dramatically enhancing recognition rate in the backlight environment
- Supports tamper alarm
- Stand-alone device, ready for networking
- Local face database management and device management
- Remote live view and two-way talk

Shenzhen TVT Digital Technology Co., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R. China

Tel: +86-755-36995888

Website: <http://en.tvt.net.cn>

Fax: +86-755-33104777

E-mail: overseas@tvt.net.cn

Specifications


Model	TD-E2128-L/TP
Performance	
OS	Embedded Linux
Storage	8Gb DDR3 +16GB EMMC
Screen	
Display Screen	8inch LCD touch screen; resolution: 1280x800; contrast: 500:1
Brightness	500 lux
Control Interface	I2C
Face Recognition	
Sensor	1/2.8
Lens	2MP dual-lens, f=3.97mm @ F1.6
Lens Mount	M12
WDR	120db
Height Range of Face Recognition	1.2m-2.2m (the recommended installation height is 1.45m, based on the tester's height of 170cm)
Face Recognition Distance	0.3m-2m (the recommended face recognition distance is from 0.5m to 1m)
Recognition Mode	Face: 1 : N
Recognition Duration	≤ 0.5 s per person
Face Capacity	20,000
Recognition Accuracy	99.7%
Supplementary Light	
IR Distance	5m
White Light Distance	1-3m (soft white light)
Smart Linkage	
Screen Wakeup	Yes
Light Adjustment	Yes
Snapshot	Yes
Audio	
Two-way Talk	Yes (noise reduction and echo cancellation)
Audio Input	1CH built-in MIC
Audio Output	Built-in speaker
Interface	

Network Interface	10/100Mbps self-adaptive Ethernet port x1
Alarm Input	2CH
Alarm Output	2 CH
Wiegand Interface	Wiegand input/output (26/34)
RS485	RS485x1 (half duplex)
Door Lock Output	Relay output, NO/NC(optional), delay setting supported
SD Card Interface	1 micro SD card slot, up to 256G
USB Interface	USB x1
Anti-Tamper Interface	1 button
Exit Button	1
Reset Button	1
Others	
Power	12V @ 1A
Power Management	Screen sleep, screen protection, time switch
Power Consumption	<10W
Weight	Approx. 1.05KG
Installation	Wall Mounting, Embedded Installation, Desktop
Protection	Surge Protection and Voltage Transient Protection
Certificate	CE, FCC
Environment Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU), directive 94/62/EC and REACH(EC1907/2006)
Working Environment	-20°C~55°C, <95% (non-condensing)
Dimensions(mm)	138.6x30.8x271

Available Model

Available Model	TD-E2128-L/TP	Indoor Face Recognition Terminal
-----------------	---------------	----------------------------------

Dimensions



Accessories

Optional:



TD-YZJ1002
Pole Mount



TD- YZJ1003
Desktop Mount



TD- YZJ1003A
Wall Mount



TD-YZJ1005
Floor-Standing Mount