

EPICa

EP-2243J-SCSC

EP-2243JD-SCSC

2U 24Bays 12Gb SAS to 12Gb SAS JBOD Enclosure Solution



The EPICa EP-2243J/JD-SCSC is a 19-inch 2U rackmount JBOD unit. It is a versatile SAS3 / SATA3 disk expansion system, ideal for high capacity and scalability storage in IT demands. The EP-2243J/JD-SCSC offers high density storage, hardware redundancy and easily integrates into versatile applications that request high performance and high scalability.

The EPICa EP-2243J/JD-SCSC comes with either dual or single JBOD controller configuration for options. It features a modular architecture for all key components which ease system maintenance and management.

Highest Density Available

- 2U chassis with 24 bays carriers
- Support the 2.5" enterprise class SAS3/SATA3 HDD/SSD drives

High Availability

- Single or dual SAS JBOD controller module
- Each SAS JBOD controller module consist of three 4x mini SAS HD ports
- DataBolt™ Bandwidth Optimizer for balance faster host and slower SAS or SATA devices

Power Supply

- Power supply and cooling system contained in 1 module for efficient cooling
- Two 400W redundant hot swappable power supplies

Enclosure

- Incorporates a cableless design for maximum signal integrity
- Utilizes industry-standard SCSI enclosure services (SES) to monitor enclosure and disk environmental conditions

Enclosure monitoring

- S.E.S. support for standard enclosure management
- System LED indications
- Fan speed monitoring
- Power supply monitoring
- System voltage monitoring
- System temperature monitoring
- System alarm



Series Technical Specifications

| | |
|------------------------------|--|
| Model | EP-2243J-SCSC / EP-2243JD-SCSC |
| JBOD Controller | Single / Redundant |
| Host Interface | One 4x mini SAS HD (12Gb/s) / Two 4x mini SAS HD (12Gb/s) |
| Disk Interface | 12Gb/s SAS, 6Gb/s SATA HDD/SSD |
| SAS expansion | Two 4x mini SAS HD (12Gb/s) / Four 4x mini SAS HD (12Gb/s) |
| Enclosure | |
| Platform | Rackmount |
| Form Factor | 2U |
| # of Hot Swap Trays | 24 x 2.5" Small Form Factor(SFF) trays |
| Disk Status Indicator | Access / Fail LED |
| Backplane | SAS / SATA Single BP |
| # of PS/Fan Modules | 400W x 2 w/PFC |
| # of Fans | 2 |
| Monitor port support | Yes |
| Power requirements | AC 90V ~ 264V Full Range, 8A ~ 4A, 47Hz ~ 63Hz |
| Environmental | |
| Relative Humidity | 10% ~ 85% Non-condensing |
| Operating Temperature | 10°C ~ 40°C (50°F ~ 104°F) |
| Physical Dimension | 559(L) x 483(W) x 88(H) mm |
| Weight (Without Disk) | 14 / 15 Kg |

Specification is subject to change without notice.

All company and product names are trademarks of their respective owners.



UNIFOSA CORP.

Tel:886-2-2914-8001(Rep.) Fax:886-2-2914-7975

<http://www.proware.com.tw> E-mail:info@proware.com.tw

Your Storage Solutions Partner